

DOCUMENT 00900

ADDENDUM

ADDENDUM NO. [1] Date: March 18, 2010

**RE: 2009 CAPITAL MAINTENANCE AND IMPROVEMENTS
 SCHOOL DISTRICT OF LA CROSSE
 LA CROSSE, WISCONSIN
 HSR PROJECT NO. L09090**

FROM: HSR Associates, Inc.
 100 Milwaukee Street
 La Crosse, WI 54603
 (608) 784-1830

TO: Prospective Bidders

This addendum forms a part of the Contract Documents and modifies the original Bidding Documents dated March 2010. Acknowledge receipt of this Addendum in the space provided on the Bid Form. Failure to do so may subject the Bidder to disqualification.

This Addendum consists of 2 typed pages and revised Bid Form (3 pages).

CHANGES TO PRIOR ADDENDA: N/A.

CHANGES TO BIDDING REQUIREMENTS: N/A

CHANGES TO CONDITIONS OF THE CONTRACT: N/A

CHANGES TO SPECIFICATIONS:

1. **Document 00410 Bid Form:** Revised Bid Form attached hereto.
2. **Unit Prices:** Unit prices shall be used in determining additions to or deductions from the Contract amount when changes in the Work as shown on the Drawings or in the Project Manual are directed. They will apply only when the changes involve materials, specifications, methods, and designs that are the same as those required in the work shown and/or specified. This will not be applied to changes requiring the use of materials, specifications, methods or design of different character from those shown or specified. The unit prices shall allow for all of Contractor's costs, including overhead and profit.

Unit Price UP-1: (Floor Filler at Abated Classroom Floors)

State the amount per cubic foot to install (at damaged floors from abatement work) minimum 2500 psi lightweight concrete or gypsum concrete leveling overlay.

Provide pour stops at required distance from doors to allow for 1/8" per foot slope of installed latex floor filler to adjacent corridor elevation.

3. **SECTION 02510 – ASPHALTIC CONCRETE PAVING**
 - a. Add the following to paragraph 2.03:
 - B.** Sealant for joint Type B shall be Nova Sports USA Novacaulk.
 - b. Add the following to paragraph 3.07:

- D. Joint Type B may be used in place of joint method specified in A through C of this paragraph. Saw cutting for joint Type B shall be in accordance with the following:
1. Depth: 1/3 of the pavement thickness if using joint filler application alternate #1. Saw the joint entirely if using joint filler application alternate #2.
 2. Width: Standard single blade with 1/8" for the full depth of the cut.
 3. Method: Sawed joint shall be cut in a single pass.
- c. Add the following to paragraph 3.8:
- E. Joint filling for joint Type B shall be in accordance with the following in place of A. through D. of this paragraph:
1. The Contractor shall notify the A/E 24 hours prior to applying joint filler.
 2. Apply undiluted Novacaulk #1 as follows:
 - a. Application Alternate #1
 1. Saw the specified joint.
 2. Clean the joint so that it is free of all debris. Remove all lost pavement from joint.
 3. Install backer rod (must be wider than the saw cut) into saw cut, top of rod 3/16" below surface of the saw cut.
 4. Use a broad knife, squeegee rubber, or similar tool, to fill the cut to refusal with Novacaulk. It is important to exert some pressure when placing the Novacaulk into the void so that the material comes in contact with the walls of the saw cut and the backer rod.
 5. Allow the Novacaulk to set. (4 hours during ideal drying conditions -longer when damp or cool).
 - b. Application Alternate #2
 1. Saw the specified joint.
 2. Clean the joint so that it is free of all debris. Remove all lost pavement from joint.
 3. Use a broad knife, squeegee rubber, or similar tool, to fill the cut full depth with Novacaulk. It is important to exert some pressure when placing the Novacaulk into the void so that the material comes in contact with the walls of the saw cut and penetrates to the full depth of the joint.
 4. Allow the Novacaulk to set. (4 hours during ideal drying conditions -longer when damp or cool).

4. **SECTION 02532 – COURT COLOR FINISH SYSTEM**

- a. Add the following Acceptable Manufacturer to paragraph 2.01:
- b. Advanced Polymer Technology, Harmony, PA, (724) 452-1330 shall be approved provided the following conditions are met:
 - (1). Laykold Colorcoat System utilizing a minimum of one application of NuSurf or Laykold Advantage System utilizing two applications of NuSurf.
 - (2). Laykold Line Prime shall be applied prior to line paint.
 - (3). Laykold color selection shall include Premium Colors.

CHANGES TO DRAWINGS: N/A

END OF DOCUMENT 00900

DOCUMENT 00410

BID FORM

BIDDER: _____

BID FOR SINGLE PRIME CONTRACT

PROJECT: **2009 CAPITAL MAINTENANCE & IMPROVEMENTS
SCHOOL DISTRICT OF LA CROSSE
LA CROSSE, WISCONSIN
HSR PROJECT NO. L09090**

TO: **SCHOOL DISTRICT OF LA CROSSE
807 EAST AVENUE SOUTH
LA CROSSE, WISCONSIN 54601**

BASE BID

The undersigned, having examined the site where the Work is to be executed and become familiar with local conditions affecting the cost of the Work and carefully examined the Project Manual, the Project Drawings, all other Bidding Documents and Addenda thereto prepared by the AE, HSR Associates, Inc., hereby agrees to provide all labor, materials, equipment and services necessary for the complete and satisfactory execution of the ENTIRE WORK, including General Construction, Plumbing, and Electrical Work for the Base Bid stipulated sum of:

_____ Dollars (\$_____ .00)

UNIT PRICES

The undersigned agrees to add or deduct portions of the Work from the Contract as described in Addendum 1, for the following Unit Price amounts:

A. Unit Price UP-1: (Pourable Floor Filler)

Per cubic foot _____ Dollars (\$_____ .00)

BIDDER'S CHOICE SUBSTITUTIONS

The following Bidder's Choice Substitution is proposed for your consideration subject to the requirements set forth in the Instructions to Bidders:

Substitution No. S1:

For substituting _____

Type, Brand, Catalog No. _____

Manufacturer _____

Deduct from BASE BID _____ Dollars (\$_____ .00)

In submitting this Bid, the undersigned agrees to:

1. Hold this Bid open for **60** days.
2. Accept the provisions of Instructions to Bidders regarding disposition of Bid Security.
3. Enter into and execute an Agreement, if awarded on the basis of this Bid, and to furnish Performance and Labor and Material Payment Bonds according to the Supplementary Conditions.
4. Accomplish work according the Contract Documents.
5. Complete the work by the time stated in Section 01010 Summary of the Work.

Receipt of the following Addenda and inclusion of their provisions in this Bid is hereby acknowledged:

Addendum No. _____ Dated _____

Addendum No. _____ Dated _____

Addendum No. _____ Dated _____

Addendum No. _____ Dated _____

Attached hereto are the required Bid Security and Certificate of Organization and Authority.

An executed Document 00441 Disclosure of Ownership is:

Attached hereto.

Not applicable to the undersigned Bidder.

BIDDER SHALL ENTER "X" IN ONE OF THE ABOVE (), AS APPLICABLE.

FIRM NAME: _____

(Affix seal if Corporation) By: _____

Title: _____

By: _____

Title: _____

Date: _____

Official Address: _____

Telephone: _____

