

**DOCUMENT 00 90 00  
ADDENDUM**

**ADDENDUM NO. [2]                      Date: November 2, 2018**

**RE:                      PRENTICE SCHOOL DISTRICT  
                            ADDITION AND REMODELING BID PKG 3  
                            1025 TOWN ST  
                            PRENTICE, WI 54556  
                            HSR PROJECT NO. 18022**

**FROM:                  HSR Associates, Inc  
                            100 Milwaukee Street  
                            La Crosse, WI 54603  
                            (608) 784-1830**

**To:                      Prospective Bidders**

This addendum forms a part of the Contract Documents and modifies the original Bidding Documents dated October 2018. Acknowledge receipt of this Addendum in the space provided on the bid form. Failure to do so may subject the Bidder to disqualification.

This Addendum consists of [2] pages, [1] specification section, and [17] 30 x 42 drawings.

**CHANGES TO BIDDING REQUIREMENTS AND CONDITIONS OF THE CONTRACT:**

1. Section 00 11 33 ADVERTISEMENT FOR BIDS
  - a. Bid date shall change from November 6 to November 13, 2018.

**GENERAL REQUIREMENTS:**

2. Section 01 21 00 ALLOWANCES
  - a. 1.07, A: Change allowance amount for brick from \$1400 to \$2000 per thousand.

**CHANGES TO SPECIFICATIONS:**

3. Section 04 72 00 CAST STONE MASONRY
  - a. Section attached hereto as part of Contract Documents.

**CHANGES TO DRAWINGS**

4. Sheet A112R FLOOR PLAN-UNIT B 30 x 42 attached hereto.
  - a. Revisions clouded on Drawing.
  - b. 6" concrete foundation wall w/ 4" brick added at NW corner of Kitchen.
5. Sheet A200R EXTERIOR ELEVATIONS 30 x 42 attached hereto
  - a. Revisions clouded on Drawing.
  - b. Cast reveals added.
  - c. Cast stone corner details added.
6. Sheet A201R EXTERIOR ELEVATIONS 30 x 42 attached hereto
  - a. Revisions clouded on Drawing

7. Sheet A310R WALL SECTIONS 30 x 42 attached hereto
  - a. Revisions clouded on Drawing
  - b. Section 11 added showing 6 inch foundation brick ledge.
8. Sheet A311R WALL SECTIONS 30 x 42 attached hereto
  - a. Revisions clouded on Drawing
9. Sheet A313R WALL SECTIONS 30 x 42 attached hereto
  - a. Revisions clouded on Drawing
10. Sheet A314R WALL SECTIONS 30 x 42 attached hereto
  - a. Revisions clouded on Drawing
11. Sheet A315R WALL SECTIONS 30 x 42 attached hereto
  - a. Revisions clouded on Drawing
12. Sheet A500 DETAILS 30 x 42 attached hereto
  - a. Drawing attached as part of Contract Documents
13. Sheet A501 DETAILS 30 x 42 attached hereto
  - a. Drawing attached as part of Contract Documents
14. Sheet A510 DOOR-WINDOW DETAILS 30 x 42 attached hereto
  - a. Drawing attached as part of Contract Documents
15. Sheet A511 DOOR-WINDOW DETAILS 30 x 42 attached hereto
  - a. Drawing attached as part of Contract Documents
16. Sheet A512 DOOR-WINDOW DETAILS 30 x 42 attached hereto
  - a. Drawing attached as part of Contract Documents
17. Sheet A513 DOOR-WINDOW DETAILS 30 x 42 attached hereto
  - a. Drawing attached as part of Contract Documents
18. Sheet A514 MISC DETAILS 30 x 42 attached hereto
  - a. Drawing attached as part of Contract Documents
19. Sheet S202R FRAMING PLANS-UNIT A&E 30 x 42 attached hereto
  - a. Revisions clouded on Drawing
20. Sheet S810R FRAMING DETAILS 30 x 42 attached hereto
  - a. Revisions clouded on Drawing

**END OF DOCUMENT 00 90 00**

**SECTION 04 72 00**  
**CAST STONE MASONRY**

**PART 1 GENERAL**

**1.01 SECTION INCLUDES**

- A. Architectural cast stone, dry cast.
- B. Units required are:
  - 1. Exterior wall units, including sills, water tables, and wall panels.

**1.02 RELATED REQUIREMENTS**

- A. Section 04 05 11 - Mortar and Masonry Grout: Mortar for setting cast stone.
- B. Section 04 20 00 - Unit Masonry: Installation of cast stone in conjunction with masonry.
- C. Section 07 92 00 - Joint Sealants: Sealing joints indicated to be left open for sealant.

**1.03 REFERENCE STANDARDS**

- A. ACI 318 - Building Code Requirements for Structural Concrete and Commentary; 2014 (Errata 2016).
- B. ASTM A123/A123M - Standard Specification for Zinc (Hot-Dip Galvanized) Coatings on Iron and Steel Products; 2015.
- C. ASTM A185/A185M - Standard Specification for Steel Welded Wire Reinforcement, Plain, for Concrete; 2007.
- D. ASTM A615/A615M - Standard Specification for Deformed and Plain Carbon-Steel Bars for Concrete Reinforcement; 2016.
- E. ASTM A767/A767M - Standard Specification for Zinc-Coated (Galvanized) Steel Bars for Concrete Reinforcement; 2009 (Reapproved 2015).
- F. ASTM A884/A884M - Standard Specification for Epoxy-Coated Steel Wire and Welded Wire Reinforcement; 2014.
- G. ASTM A1064/A1064M - Standard Specification for Carbon-Steel Wire and Welded Wire Reinforcement, Plain and Deformed, for Concrete; 2015.
- H. ASTM C33/C33M - Standard Specification for Concrete Aggregates; 2016.
- I. ASTM C150/C150M - Standard Specification for Portland Cement; 2016.
- J. ASTM C 173 - Standard Test Method for Air Content of Freshly Mixed Concrete by the Volume Method.
- K. ASTM C 231 - Standard Test Method for Air Content of Freshly Mixed Concrete by the Pressure Method.
- L. ASTM C 260 - Standard Specification for Air-Entrained Admixtures for Concrete.
- M. ASTM C270 - Standard Specification for Mortar for Unit Masonry; 2014a.
- N. ASTM C494/C494M - Standard Specification for Chemical Admixtures for Concrete; 2016.
- O. ASTM C 618 – Specification for Coal Fly Ash and Raw or Calcined Natural Pozzolan for Use as a Mineral Admixture in Concrete.
- P. ASTM C642 - Standard Test Method for Density, Absorption, and Voids in Hardened Concrete; 2013.
- Q. ASTM C 666 – Standard Test Method for Resistance of Concrete to Rapid Freezing and Thawing.
- R. ASTM C979/C979M - Standard Specification for Pigments for Integrally Colored Concrete; 2016.
- S. ASTM C 989 – Standard Specification for Ground Granulated Blast-Furnace Slag for Use in Concrete.
- T. ASTM C 1194 - Standard Test Method for Compressive Strength of Architectural Cast Stone.
- U. ASTM C 1195 - Standard Test Method for Absorption of Architectural Cast Stone
- V. ASTM C1364 - Standard Specification for Architectural Cast Stone; 2017.
- W. ASTM D 2244 – Standard Test Method for Calculation of Color Differences from Instrumentally Measured Color Coordinates.

#### 1.04 DEFINITIONS

- A. Cast Stone - a refined architectural concrete building unit manufactured to simulate natural cut stone, used in unit masonry applications.
  - 1. Dry Cast Concrete Products – manufactured from zero slump concrete.
    - a. Vibrant Dry Tamp (VDT) casting method: Vibratory ramming of earth moist, zero- slump concrete against a rigid mold until it is densely compacted.
    - b. Machine casting method: manufactured from earth moist, zero-slump concrete compacted by machinery using vibration and pressure against a mold until it becomes densely consolidated
  - 2. Wet Cast Concrete Products – manufactured from measurable slump concrete.
    - a. Wet casting method: manufactured from measurable slump concrete and vibrated into a mold until it becomes densely consolidated.

#### 1.05 SUBMITTALS

- A. See Section 01 30 00 - Administrative Requirements, for submittal procedures.
- B. Product Data: Test results of cast stone components made previously by the manufacturer.
- C. Shop Drawings: Include key plans, elevations, floor plans when appropriate, dimensions, layouts, profiles, cross sections, reinforcement, exposed faces, arrangement of joints, anchoring methods, anchors, and piece numbers.
- D. Test results: Submit manufacturers test results of Cast Stone previously made by the manufacturer in the last 90 days, for the following.
  - 1. Compressive Strength
  - 2. Absorption
  - 3. Air Content (wet cast only)
- E. Verification Samples: (2) pieces of actual cast stone components not less than 12 inches square, illustrating range of color and texture to be anticipated in components furnished for the project.
- F. Source Quality Control Test Reports.
- G. Manufacturer's Qualification Data: Documentation showing compliance with specified requirements.

#### 1.06 QUALITY ASSURANCE

- A. Manufacturer Qualifications:
  - 1. A firm with a minimum of 10 years experience producing cast stone of types required for project.
  - 2. Current producer member of the Cast Stone Institute in good standing.
  - 3. Manufacturer's production facility currently holds a Plant Certification from the Cast Stone Institute.
  - 4. Adequate plant capacity to furnish quality, sizes, and quantity of cast stone required without delaying progress of the work.
  - 5. All products must contain Portland cement.
- B. Mock-Up: Provide full size cast stone components for installation in mock-up of exterior wall.
  - 1. Approved mock-up will become standard for appearance and workmanship.

#### 1.07 DELIVERY, STORAGE, AND HANDLING

- A. Deliver cast stone components secured to shipping pallets and protected from damage and discoloration. Protect corners from damage.
- B. Number each piece individually to match shop drawings and schedule.
- C. Store cast stone components and installation materials in accordance with manufacturer's instructions.
- D. Store cast stone components on pallets with nonstaining, waterproof covers. Ventilate under covers to prevent condensation. Prevent contact with dirt.
- E. Protect cast stone components during handling and installation to prevent chipping, cracking, or other damage.
- F. Store mortar materials where contamination can be avoided.
- G. Schedule and coordinate production and delivery of cast stone components with unit masonry work to optimize on-site inventory and to avoid delaying the work.

## **PART 2 PRODUCTS**

### **2.01 MANUFACTURERS**

- A. Architectural Cast Stone:
  - 1. Any current producer member of the Cast Stone Institute.
  - 2. Edwards Cast Stone: [www.edcstone.com](http://www.edcstone.com).
  - 3. American Artstone: [www.american-artstone.com](http://www.american-artstone.com).
  - 4. MidCon Products: [www.midconproducts.com](http://www.midconproducts.com)
  - 5. Custom Cast Stone: [www.customcaststone.com](http://www.customcaststone.com)

### **2.02 ARCHITECTURAL CAST STONE**

- A. Cast Stone: Architectural concrete product manufactured to simulate appearance of natural stone, complying with ASTM C1364.
  - 1. Compressive Strength: As specified in ASTM C 1194 and C 1364; 6500 psi minimum for products at 28 days.
  - 2. Water absorption: ASTM C 1195: 6% maximum by the cold water method, or 10% maximum by the boiling method for products at 28 days.
  - 3. Air Content – ASTM C173 or C 231, for wet cast product shall be 4-8% for units exposed to freeze-thaw environments. Air entrainment is not required for VDT products.
  - 4. Freeze-Thaw Resistance: Demonstrated by laboratory testing in accordance with ASTM C 1364. The CPWL shall be less than 5% after 300 cycles of freezing and thawing.
  - 5. Linear Shrinkage – ASTM C 426: Shrinkage shall not exceed 0.065%.
  - 6. Surface Texture: Fine grained texture, with no bugholes, air voids, or other surface blemishes visible from distance of 20 feet.
  - 7. Color: Selected by Architect from manufacturer's full range.
- B. Shapes: Provide shapes indicated on drawings.
  - 1. Variation from Any Dimension, Including Bow, Camber, and Twist: Maximum of plus/minus 1/8 inch or length divided by 360, whichever is greater, but not more than 1/4 inch.
  - 2. Unless otherwise indicated on drawings, provide:
    - a. Wash or slope of 1:12 on exterior horizontal surfaces.
    - b. Drips on projecting components, wherever possible.
    - c. Raised fillets at back of sills and at ends to be built in.
- C. Reinforcement: Provide reinforcement as required to withstand handling and structural stresses; comply with ACI 318.
  - 1. Pieces More than 12 inches Wide: Provide full length two-way reinforcement of cross-sectional area not less than 0.25 percent of unit cross-sectional area.
- D. Reinforcement shall be noncorrosive where faces exposed to weather are covered with less than 1.5 in. of concrete material. All reinforcement shall have minimum coverage of twice the diameter of the bars.
- E. Panels, soffits and similar stones greater than 24 in. (600 mm) in one direction shall be reinforced in that direction. Units less than 24 in. (600 mm) in both their length and width dimension shall be non-reinforced unless otherwise specified.
- F. Welded wire fabric reinforcing shall not be used in dry cast products.

### **2.03 MATERIALS**

- A. Portland Cement: ASTM C150/C150M.
  - 1. For Units: Type I or II, white or grey.
  - 2. For Mortar: Type I or II, except Type III may be used in cold weather.
- B. Coarse Aggregate: ASTM C33/C33M, except for gradation; granite, quartz, or limestone.
- C. Fine Aggregate: ASTM C33/C33M, except for gradation; natural or manufactured sands.
- D. Pigments: ASTM C979, inorganic iron oxides; do not use carbon black.
- E. Admixtures:
  - 1. ASTM C 260 for air entraining admixtures.
  - 2. ASTM C 494/C 494M Types A-G for water reducing, retarding, accelerating and high range admixtures.
  - 3. Other admixtures: integral water repellents and other chemicals, for which no ASTM Standard exists, shall be previously established as suitable for use in concrete by proven field performance or through laboratory testing.

4. ASTM C 618 mineral admixtures of dark and variable colors shall not be used in surfaces intended to be exposed to view.
  5. ASTM C 989 granulated blast furnace slag may be used to improve physical properties. Tests are required to verify these features.
- F. Water: Potable.
- G. Reinforcing:
1. ASTM A 615/A 615M. Grade 40 or 60 steel galvanized or epoxy coated when cover is less than 1.5 in.
  2. Welded Wire Fabric: ASTM A 185/A where applicable for wet cast units.
  3. All anchors, dowels and other anchoring devices and shims shall be standard building stone anchors commercially available in a non-corrosive material such as zinc plated, galvanized steel, brass, or stainless steel Type 302 or 304.
- H. Reinforcing Bars: ASTM A615/A615M deformed bars, galvanized.
1. Galvanized in accordance with ASTM A767/A767M, Class I.
- I. Steel Welded Wire Reinforcement: ASTM A1064/A1064M, galvanized or ASTM A884/A884M, epoxy coated.
- J. Embedded Anchors, Dowels, and Inserts: Type 304 stainless steel, of type and size as required for conditions.
- K. Shelf Angles and Similar Structural Items: Hot-dip galvanized steel per ASTM A123/A123M, of shapes and sizes as required for conditions.
- L. Prefab corners as recommended by supplier.
- M. Mortar: Portland cement-lime; do not use masonry cement.
- N. Sealant: As specified in Section 07 92 00.
- O. Flashings: Type as specified in Section 04 20 00.
- P. Cleaner: Approved for intended use by cast stone manufacturer and by cleaner manufacturer for use on cast stone and adjacent masonry materials.

#### **2.04 COLOR AND FINISH**

- A. Match approved sample.
- B. All surfaces intended to be exposed to view shall have a fine-grained texture similar to natural stone, with no air voids in excess of 1/32 in. (0.8 mm) and the density of such voids shall be less than 3 occurrences per any 1 in.2 (25 mm<sup>2</sup>) and not obvious under direct daylight illumination at a 5 ft (1.5m) distance.
- C. All exposed edges to be hand tooled to ensure a consistent quality edge.
- D. Units shall exhibit a texture equal to the approved sample when viewed under direct daylight illumination at a 10 ft (3 m) distance.
1. ASTM D 2244 permissible variation in color between units of comparable age subjected to similar weathering exposure.
    - a. Total color difference - not greater than 6 units.
    - b. Total hue difference - not greater than 2 units.
- E. All Cast Stone shall be hand sanded and acid washed with a 10% muriatic acid solution.
- F. The occurrence of crazing or efflorescence shall not constitute a cause for rejection.

#### **2.05 SOURCE QUALITY CONTROL**

- A. Production Testing:
1. Test compressive strength and absorption of specimens selected at random from plant production.
  2. Test in accordance with ASTM C642 ASTM C 1194 and C 1195.
  3. Samples shall be taken and tested from every 500 cubic feet of product produced.
  4. New and existing mix designs shall be tested for strength, absorption and freeze thaw compliance prior to producing units.

- B. Job Site Testing: One (1) sample from production units shall be selected at random from the field for each 500 cubic feet delivered to the job site.
  - 1. Three (3) field cut cube specimens from each of these samples shall have an average minimum compressive strength of not less than 85% with no single specimen testing less than 75% of design strength as allowed by ACI 318.
  - 2. Three (3) field cut cube specimens from each of these samples shall have an average maximum cold-water absorption of 6%.
  - 3. Field specimens shall be tested in accordance with ASTM C 1194 and C 1195.
  - 4. Submit reports of tests by independent testing agency, showing compliance with requirements.

### **PART 3 EXECUTION**

#### **3.01 EXAMINATION**

- A. Examine construction to receive cast stone components. Notify Architect if construction is not acceptable.
- B. Do not begin installation until unacceptable conditions have been corrected.

#### **3.02 INSTALLATION**

- A. Install cast stone components in conjunction with masonry, complying with requirements of Section 04 20 00.
- B. Mechanically anchor cast stone units indicated; set remainder in mortar.
- C. Setting:
  - 1. Drench cast stone components with clear, running water immediately before installation.
  - 2. Set units in a full bed of mortar unless otherwise indicated.
  - 3. Fill vertical joints with mortar.
  - 4. Fill dowel holes and anchor slots completely with mortar or non-shrink grout.
- D. Joints: Make all joints 3/8 inch, except as otherwise detailed.
  - 1. Rake mortar joints 3/4 inch for pointing.
  - 2. Remove excess mortar from face of stone before pointing joints.
  - 3. Point joints with mortar in layers 3/8 inch thick and tool to a slight concave profile.
  - 4. Leave the following joints open for sealant:
    - a. Head joints in top courses, including copings, parapets, cornices, sills, and steps.
    - b. Joints in projecting units.
    - c. Joints between rigidly anchored units, including soffits, panels, and column covers.
    - d. Joints below lugged sills and stair treads.
    - e. Joints below ledge and relieving angles.
    - f. Joints labeled "expansion joint".
- E. Sealant Joints: Install sealants as specified in Section 07 92 00.
- F. Installation Tolerances:
  - 1. Variation from Plumb: Not more than 1/8 inch in 10 feet or 1/4 inch in 20 feet or more.
  - 2. Variation from Level: Not more than 1/8 inch in 10 feet or 1/4 inch in 20 feet, or 3/8 inch maximum.
  - 3. Variation in Joint Width: Not more than 1/8 inch in 36 inches or 1/4 of nominal joint width, whichever is less.
  - 4. Variation in Plane Between Adjacent Surfaces (Lipping): Not more than 1/16 inch difference between planes of adjacent units or adjacent surfaces indicated to be flush with units.
- G. Repairs: Repair chips and other surface damage noticeable when viewed in direct daylight at 20 feet.
  - 1. Repair with matching touchup material provided by the manufacturer and in accordance with manufacturer's instructions.
  - 2. Repair methods and results subject to Architect 's approval.

#### **3.03 TOLERANCES**

- A. Cross section dimensions shall not deviate by more than  $\pm 1/8$  in. from approved dimensions.
- B. Length of units shall not deviate by more than length/ 360 or  $\pm 1/8$  in., whichever is greater, not to exceed  $\pm 1/4$  in. (6 mm).
  - 1. Maximum length of any unit shall not exceed 12 times the average thickness of such unit unless otherwise agreed by the manufacturer

- C. Warp, bow or twist of units shall not exceed length/ 360 or  $\pm 1/8$  in. (3 mm), whichever is greater.
- D. Location of dowel holes, anchor slots, flashing grooves, false joints and similar features; on formed sides of unit, 1/8 in. (3 mm), on unformed sides of unit, 3/8 in. (9 mm) maximum deviation.

#### **3.04 CLEANING**


- A. Clean completed exposed cast stone after mortar is thoroughly set and cured.
  - 1. Wet surfaces with water before applying cleaner.
  - 2. Apply cleaner to cast stone in accordance with manufacturer's instructions.
  - 3. Remove cleaner promptly by rinsing thoroughly with clear water.
  - 4. Do not use acidic cleaners.

**END OF SECTION**





Consultant:



**1 FLOOR PLAN- UNIT B**  
1/8" = 1'-0"

**GENERAL NOTES:**

- A SEE ID SHEETS FOR FLOOR AND WALL FINISH LAYOUTS.
- B LOOSE FURNISHINGS EXCEPT AS NOTED SHALL BE PROVIDED AND INSTALLED BY THE OWNER.
- C VERIFY EXACT SIZE AND LOCATION OF ALL MECHANICAL / PLUMB AND ELEC OPENINGS - GENERAL CONTRACTOR SHALL BE RESPONSIBLE FOR FINISH AT ALL VISIBLE AREAS. ALL OPENING SHALL BE SEALED AFTER UTILITY INSTALLATION.
- D PAINT ALL EXPOSED STEEL LINTELS.
- E INSTALL BULLNOSE CMU AT ALL OUTSIDE CORNERS W/O TILE AND AT DOOR JAMBS AS DETAILED. NO BULLNOSE AT WINDOW JAMBS.
- F SEE STRUCTURAL FOR SLAB CONTROL JOINTS.
- G SEE A510 FOR WALL CONTROL JOINT DETAILS. SEE PLANS AND ELEVATIONS FOR CJ LOCATIONS. CJ = CONTROL JOINTS.
- H REFER TO CODE PLANS FOR FIRE RATING LOCATIONS AND ACCESSIBILITY ROUTES.
- J EXTEND ALL WALLS TO DECK UNLESS NOTED OTHERWISE. SEE A601 FOR TOP OF WALL DETAILS.
- K UNLESS NOTED OTHERWISE RESTROOM FLOORS SHALL BE SLOPED A MIN. 1/16" - 1/2" TO FLOOR DRAINS - TO "CENTER", IF NO FLOOR DRAINS.
- L SEE A512 FOR TYPICAL HEAD FLASHING AND THROUGH-WALL FLASHING ISOMETRIC DETAILS.
- M GEN. CONTRACTOR TO PROVIDE CONC. EQUIP. PADS/CURBS AS REQUIRED FOR MECHANICAL EQUIP. - VERIFY SIZE/PROFILE/LOCATION WITH MECHANICAL.
- N PLAN DIMENSIONS ARE FROM FACE OF WALL TO FACE OF WALL.
- P ALL DOOR FRAMES TO BE 4" FROM CORNERS UNLESS NOTED OTHERWISE.

**LEGEND:**

- (A) SYMBOL INDICATES WALL TYPE - SEE SHEET A601 FOR WALL TYPE DETAILS.
- (W) SYMBOL INDICATES WINDOW TYPE. SEE SHEET A602 FOR WINDOW FRAME ELEVATIONS.
- (C) SYMBOL INDICATES CONSTRUCTION NOTE THIS SHEET
- 1 HOUR WALL
- 2 HOUR WALL
- COL EXISTING STEEL COLUMN
- EWC ELECTRIC WATER COOLER
- FE FIRE EXTINGUISHER- BRACKET MOUNTED
- FEC FIRE EXTINGUISHER CABINET
- MB-11" MARKER BOARD- 48" HIGH x LENGTH INDICATED ON PLAN
- SB SMART BOARD
- SWB SLOTTED WALL BOARD- 24" HIGH x LENGTH INDICATED ON PLAN
- TB TACK BOARD- 48" HIGH x 48" WIDE
- TS-11" TACK STRIPS- MOUNT (1) AT 44" AFF AND (1) AT 84" AFF x LENGTH INDICATED ON PLAN

**KEY NOTES PLAN**

- 1 INFILL EXISTING OPENING WITH CMU. MATCH ADJACENT FINISHES.
- 2 NEW FOLDING PANEL PARTITION.
- 3 INFILL EXISTING SLAB DEPRESSION.
- 4 FLOOR OPENING INFILL. SEE
- 5 PERMANENTLY SECURE EXISTING TUNNEL ACCESS PANELS.
- 6 RELOCATED DOOR/ TRANSOM.
- 7 LINE OF CANOPY ABOVE.
- 8 NEW CHEM COUNTERTOP, INTEGRAL SINK, GAS VALVES AND ELECTRICAL OUTLETS. SEE CASEWORK DRAWINGS, PLUMBING AND ELECTRICAL.
- 9 LINE OF BULKHEAD ABOVE.
- 10 VENDING MACHINES (N.I.C.)
- 11 NEW COOLER. SEE FOOD SERVICE SHEETS.
- 12 NEW DISHWASHER. SEE FOOD SERVICE SHEETS.
- 13 MOBILE STAGE (N.I.C.)
- 14 INFILL FLOOR AS REQUIRED AFTER REMOVAL OF CMU WALL. PREPARE FOR NEW FLOORING.
- 15 12"W x 19"D LOCKERS ON 4" CONCRETE SLAB.
- 16 12"W x 19"D CUBBIES ON 4" CONCRETE SLAB.
- 17 PROVIDE 3/4" PLYWOOD PANEL. COORDINATE SIZE AND MOUNTING HT WITH ELECTRICAL.
- 18 STEEL COLUMN. SEE STRUCTURAL.
- 19 MOP SINK. SEE PLUMBING.
- 20 ROOF DRAIN LEADER. SEE PLUMBING AND DETAILS A512.
- 21 SOLID SURFACE SILL.
- 22 REMOVABLE RAILINGS.
- 23 DIMENSION INDICATES PRECAST PANEL OVERHANG AT FOUNDATION BELOW. SEE DETAIL 11A200.
- 24 CONCRETE STUOP. SEE STRUCTURAL.
- 25 4 3/4" FLOOR INFILL TO MATCH HEIGHT OF GYM FLOOR. SEE DETAIL A6A14.
- 26 STUD AND GYP BD COLUMN ENCLOSURE. SEE 7A514.
- 27 CHAIR LIFT
- 28 INFILL OPENING TO MATCH EXISTING EXTERIOR WALL.
- 29 RAMP- 16% SLOPE
- 30 RAMP- 8.3% SLOPE
- 31 PERFORATED WINDOW BLINDS
- 32 INSTALL SOUNDPROOFING FLOOR MAT AND 4 x 8 x 3/4" PLYWOOD ON EXISTING STAGE. PAINT BLACK.
- 33 SHADED LINES INDICATE LOCATION OF IN-FLOOR HEATING. SEE 6A514.
- 34 LINE OF SKYLIGHT ABOVE.
- 35 EXISTING SLOPED SILL TO REMAIN (NON ADA).
- 36 CABINET HEATER. SEE MECH SHEETS.
- 37 CANOPY COLUMN. SEE
- 38 EXISTING DATA CABINET.
- 39 ROOM DARKENING SHADES.
- 40 PLAM SHELVES IN EXISTING WINDOW AND DOOR OPENINGS.
- 41 LINE OF AWNING ABOVE. SEE
- 42 PAD ALL WALLS. FLOOR TO 6'-0" AFF.
- 43 6" STUDS CHASE AT VENT PIPE LOCATIONS- COORDINATE WITH PLUMBING.
- 44 NEW CURTAINS AND STAGE RIGGING- SEE SPECS.

PRENTICE SCHOOL DISTRICT  
ADDITION AND REMODELING


Project Title: PRENTICE SCHOOL DISTRICT  
ADDITION AND REMODELING  
Project Location: 1025 Town Street  
Prentice, WI 54656  
Sheet Title: FLOOR PLAN- UNIT B

HSR Project Number: 18022

Project Date: OCTOBER 19, 2018

Drawn By: MPL

Key Plan:



Revisions:

No.	Description	Date
1	ADD 1	10-25-18
2	ADD 2	11-02-18

Graphic Scale: VARIES

Last Update: 11/2/2018 10:56:49 AM

**A112R**  
BID PACKAGE 3  
ADDENDUM 2

**BID PACKAGE 3**



Consultant:

Project Title: PRENTICE SCHOOL DISTRICT  
ADDITION AND REMODELING  
Project Location: 1025 Town Street  
Prentice, WI 54556  
Sheet Title: EXTERIOR ELEVATIONS

HSR Project Number: 18022

Project Date: OCTOBER 19, 2018

Drawn By: MPL

Key Plan:

No.	Description	Date
2	ADD 2	11-02-18

Graphic Scale: VARIES

Last Update: 11/2/2018 10:56:56 AM

**A200R**  
BID PACKAGE 3  
ADDENDUM 2


GENERAL NOTES:	
A	SEE DETAILS A200 FOR CONTROL JOINT (CJ) AND BRICK CONTROL JOINT (BCJ) INFORMATION.
B	BRICK COURSING: RUNNING 1/3 BOND TYPICAL.
C	BRICK SIZE: 4x4x12 (NOMINAL)
D	SEE SPECIFICATION FOR MATERIAL TYPE.
E	SEE DETAIL 11/A512 FOR TYPICAL HEAD FLASHING DETAIL.


LEGEND:	
△	KEYNOTE TAG
A	METAL PANEL - COLOR A
B	METAL PANEL - COLOR B
○	WINDOW TAG, SEE SHEET A212 FOR FRAME ELEVATIONS
CJ	THROUGH WALL CONTROL JOINT - SEE DETAILS A510
BCJ	BRICK VENEER CONTROL JOINT - SEE DETAILS A510
[Pattern]	METAL PANEL
[Pattern]	ARCHITECTURAL CAST STONE PANEL - SEE 8/A200 FOR REVEAL PROFILE
[Pattern]	FIELD BRICK RUNNING BOND
[Pattern]	ACCENT BAND BRICK ROWLOCK
[Symbol]	SEE WINDOW ELEV
[Symbol]	CAST STONE SILL - SEE 8/A200 FOR TYPICAL PROFILE. SEE SPEC FOR MINIMUM LENGTHS.


KEY NOTES ELEVATION	
1	PREFINISHED SHEET METAL CAP FLASHING W/ 6" WIDE JOINT COVERS SET IN SEALANT.
2	CONCRETE STOOP SLAB AT DOOR: SEE STRUCTURAL.
3	CAST STONE SILL: SEE PROFILE 8/A200.
4	METAL AWNING: SEE DETAILS.
5	OVERFLOW SCUPPER: SEE ROOF PLAN AND DETAIL SHEET.
6	SPRINKLER RISER CONNECTION.
7	COVER: SEE MECHANICAL.
8	CANOPY COLUMN: SEE DETAILS.
9	MAIN CANOPY: SEE DETAILS.
10	BUILDING SIGNAGE: BY OWNER.
11	ARCHITECTURAL PRECAST PANELS TO BE 2'-0" WIDE, UNLESS SHOWN OTHERWISE.
12	RUN EPDM UP PARAPET.
13	EXTERIOR LIGHTING.
14	SAWTOOTH IN BRICK AT EXISTING OPENING. MATCH ADJACENT BRICK.
15	REPAIR/ REPLACE METAL CAP FLASHING AS REQUIRED.
16	EXISTING METAL CAP FLASHING AND DRIP EDGE TO REMAIN.
17	CLEAN/ REPAIR EXISTING BRICK.
18	Elev.
19	Elev.
20	Elev.




**1** SEGMENT C- WEST ELEVATION  
1/8" = 1'-0"




**2** SEGMENT C- SOUTH 1  
1/8" = 1'-0"




**3** SEGMENT C- EAST 1  
1/8" = 1'-0"




**4** SEGMENT C- WEST 1  
1/8" = 1'-0"




**5** SEGMENT C- NORTH ELEVATION  
1/8" = 1'-0"




**6** SEGMENT C- SOUTH 2  
1/8" = 1'-0"




**7** SEGMENT C- EAST ELEVATION  
1/8" = 1'-0"




**8** CAST STONE SILL PROFILES  
1 1/2" = 1'-0"




**9** CAST STONE REVEAL  
3" = 1'-0"



**10** EXPANSION JOINT DETAIL  
1 1/2" = 1'-0"



**11** PRECAST CORNER DETAIL  
1/2" = 1'-0"



ELEVATION KEY PLAN

**BID PACKAGE 3**



Consultant:

PRENTICE SCHOOL DISTRICT  
ADDITION AND REMODELING  
Project Location: 1025 Town Street  
Prentice, WI 54556  
Sheet Title: EXTERIOR ELEVATIONS

HSR Project Number: 18022

Project Date: OCTOBER 19, 2018

Drawn By: Author

Key Plan:

No.	Description	Date
2	ADD 2	11-02-18

Graphic Scale: VARIES

Last Update: 11/2/2018 10:57:03 AM

**A201R**  
BID PACKAGE 3  
ADDENDUM 2

**GENERAL NOTES:**


- SEE DETAILS A200 FOR CONTROL JOINT (CJ) AND BRICK CONTROL JOINT (BCJ) INFORMATION.
- BRICK COURSING: RUNNING 1/3 BOND TYPICAL.
- BRICK SIZE: 4x4x12 (NOMINAL).
- SEE SPECIFICATION FOR MATERIAL TYPE.
- SEE DETAIL 11/A512 FOR TYPICAL HEAD FLASHING DETAIL.

**LEGEND:**

- KEYNOTE TAG
- METAL PANEL - COLOR A
- METAL PANEL - COLOR B
- WINDOW TAG, SEE SHEET A212 FOR FRAME ELEVATIONS
- THROUGH WALL CONTROL JOINT - SEE DETAILS A510
- BRICK VENEER CONTROL JOINT - SEE DETAILS A510
- METAL PANEL
- FIELD BRICK RUNNING BOND
- ARCHITECTURAL CAST STONE PANEL - SEE 9/A200 FOR REVEAL PROFILE
- ACCENT BAND BRICK ROWLOCK
- SEE WINDOW ELEV
- CAST STONE SILL - SEE 9/A200 FOR TYPICAL PROFILE. SEE SPEC FOR MINIMUM LENGTHS.


**KEY NOTES ELEVATION**

- PREFINISHED SHEET METAL CAP FLASHING W/ 6" WIDE JOINT COVERS SET IN SEALANT.
- CONCRETE STOOP SLAB AT DOOR. SEE STRUCTURAL.
- CAST STONE SILL - SEE PROFILE 9/A200.
- METAL AWNING. SEE DETAILS.
- OVERFLOW SCUPPER. SEE ROOF PLAN AND DETAIL SHEET.
- SPRINKLER RISER CONNECTION.
- LOUVER - SEE MECHANICAL.
- CANOPY COLUMN. SEE DETAILS.
- MAIN CANOPY. SEE DETAILS.
- BUILDING SIGNAGE. BY OWNER.
- ARCHITECTURAL PRECAST PANELS TO BE 2'-0" WIDE, UNLESS SHOWN OTHERWISE.
- RUN EPDM UP PARAPET.
- EXTERIOR LIGHTING.
- SAWTOOTH IN BRICK AT EXISTING OPENING. MATCH ADJACENT BRICK.
- REPAIR/ REPLACE METAL CAP FLASHING AS REQUIRED.
- EXISTING METAL CAP FLASHING AND DRIP EDGE TO REMAIN.
- CLEAN/ REPAIR EXISTING BRICK.
- Elev.
- Elev.
- Elev.




**1 MAIN ENTRY EAST**  
1/8" = 1'-0"


**2 SEGMENT D- EAST**  
1/8" = 1'-0"




**3 SEGMENT D- SOUTH**  
1/8" = 1'-0"




**4 SEGMENT D- NORTH**  
1/8" = 1'-0"




**5 MEZZANINE- NORTH**  
1/8" = 1'-0"



**6 MEZZANINE- WEST**  
1/8" = 1'-0"




**7 MEZZANINE- CHORAL/ BAND SOUTH**  
1/8" = 1'-0"




**8 FITNESS WEST**  
1/8" = 1'-0"

**ALTERNATE**



**9 SEGMENT B- NORTH**  
1/8" = 1'-0"



**ELEVATION KEY PLAN**

**BID PACKAGE 3**



Consultant:

PRENTICE SCHOOL DISTRICT  
ADDITION AND REMODELING

Project Location: 1025 Town Street  
Prentice, WI 54556

WALL SECTIONS

Project Title:

Project Number: 18022

Project Date: OCTOBER 19, 2018

Drawn By: MPL

Key Plan:


**BID PACKAGE 3**

No.	Description	Date
2	ADD 2	11-02-18


Graphic Scale: VARIES

Last Update: 11/2/2018 10:57:08 AM

**A310R**  
BID PACKAGE 3  
ADDENDUM 2



**1** EXTG WALL SECTION 1/2" = 1'-0"    **2** EXTG CORR. SECTION 1/2" = 1'-0"    **3** EXTG CORR. SECTION 1/2" = 1'-0"    **4** WALL SECTION 1/2" = 1'-0"



**5** WALL SECTION 1/2" = 1'-0"    **6** WALL SECTION 1/2" = 1'-0"    **7** WALL SECTION 1/2" = 1'-0"    **8** WALL SECTION 1/2" = 1'-0"    **9** PENTHOUSE SECTION 1/2" = 1'-0"    **10** PENTHOUSE SECTION 1/2" = 1'-0"

**11** WALL SECTION  
1/2" = 1'-0"



Consultant:

PRENTICE SCHOOL DISTRICT  
ADDITION AND REMODELING

Project Location: 1025 Town Street  
Prentice, WI 54556

Sheet Title: WALL SECTIONS

HSR Project Number: 18022

Project Date: OCTOBER 19, 2018

Drawn By: MPL

Key Plan:

No.	Description	Date
2	ADD 2	11-02-18


Graphic Scale: VARIES

Last Update: 11/2/2018 10:57:13 AM


**A311R**

BID PACKAGE 3  
ADDENDUM 2


**BID PACKAGE 3**




**5** WALL SECTION  
1/2" = 1'-0"




**4** WALL SECTION  
1/2" = 1'-0"




**3** WALL SECTION  
1/2" = 1'-0"




**2** WALL SECTION  
1/2" = 1'-0"




**1** WALL SECTION  
1/2" = 1'-0"




**11** WALL SECTION  
1/2" = 1'-0"




**10** WALL SECTION  
1/2" = 1'-0"




**9** WALL SECTION  
1/2" = 1'-0"



**8** WALL SECTION  
1/2" = 1'-0"



**7** WALL SECTION  
1/2" = 1'-0"



**6** PENTHOUSE SECTION  
1/2" = 1'-0"



Consultant:

PRENTICE SCHOOL DISTRICT  
ADDITION AND REMODELING

Project Location: 1025 Town Street  
Prentice, WI 54556

Sheet Title: WALL SECTIONS

HSR Project Number: 18022

Project Date: OCTOBER 19, 2018

Drawn By: MPL


Key Plan:

No.	Description	Date
2	ADD 2	11-02-18

Graphic Scale: VARIES

Last Update: 11/2/2018 10:57:16 AM

**A313R**  
BID PACKAGE 3  
ADDENDUM 2




**1** WALL SECTION  
1/2" = 1'-0"

**2** WALL SECTION  
1/2" = 1'-0"


**3** WALL SECTION  
1/2" = 1'-0"

**4** WALL SECTION  
1/2" = 1'-0"

**5** WALL SECTION  
1/2" = 1'-0"



**6** STAIR/ RAMP SECTION  
1/2" = 1'-0"



**7** LANDING SECTION  
1/2" = 1'-0"

**BID PACKAGE 3**



Consultant:

PRENTICE SCHOOL DISTRICT  
ADDITION AND REMODELING

Project Location: 1025 Town Street  
Prentice, WI 54556

Sheet Title: WALL SECTIONS

HSR Project Number: 18022

Project Date: OCTOBER 19, 2018

Drawn By: MPL

Key Plan:


No.	Description	Date
2	ADD 2	11-02-18

Graphic Scale: VARIES


Last Update: 11/2/2018 10:57:20 AM

**A314R**  
BID PACKAGE 3  
ADDENDUM 2


**BID PACKAGE 3**




**1** WALL SECTION  
1/2" = 1'-0"




**2** WALL SECTION  
1/2" = 1'-0"




**3** ALCOVE SECTION  
1/2" = 1'-0"




**4** STAIR SECTION  
1/2" = 1'-0"




**5** STAGE SECTION  
1/2" = 1'-0"




**6** GYM VEST. SECTION  
1/2" = 1'-0"




**7** GYM VEST. SECTION  
1/2" = 1'-0"



**8** GYM VEST. SECTION  
1/2" = 1'-0"



**9** GYM VEST. SECTION  
1/2" = 1'-0"



**10** GYM VEST. SECTION  
1/2" = 1'-0"



Consultant:

Project Title: PRENTICE SCHOOL DISTRICT  
ADDITION AND REMODELING

Project Location: 1025 Town Street  
Prentice, WI 54556

Sheet Title: WALL SECTIONS

HSR Project Number: 18022

Project Date: OCTOBER 19, 2018

Drawn By: MPL

Key Plan:

No.	Description	Date
2	ADD 2	11-02-18


Graphic Scale: VARIES

Last Update: 11/2/2018 10:57:21 AM

**A315R**

BID PACKAGE 3  
ADDENDUM 1

**BID PACKAGE 3**




**1** MAIN ENTRY CANOPY SECTION  
1/2" = 1'-0"

**2** MAIN ENTRY WALL SECTION  
1/2" = 1'-0"

**3** WALL SECTION  
1/2" = 1'-0"

**4** WALL SECTION  
1/2" = 1'-0"



**5** A315-5  
1/2" = 1'-0"







Consultant:

PRENTICE SCHOOL DISTRICT  
ADDITION AND REMODELING

Project Location: 1025 Town Street  
Prentice, WI 54556

DETAILS

HSR Project Number: 18022

Project Date: OCTOBER 19, 2018

Drawn By: MPL/JTD

Key Plan:


No.	Description	Date

Graphic Scale: VARIES


Last Update: 11/2/2018 10:57:29 AM

**A501**  
BID PACKAGE 3  
ADDENDUM 2


**BID PACKAGE 3**




**5** ROOF PARAPET DETAIL  
1 1/2" = 1'-0"




**4** WALL DETAIL  
1 1/2" = 1'-0"




**3** ROOF PARAPET DETAIL  
1 1/2" = 1'-0"




**2** ROOF DETAIL  
1 1/2" = 1'-0"




**1** ROOF DETAIL  
1 1/2" = 1'-0"




**10** MEZZAINE WALL DETAIL  
1 1/2" = 1'-0"




**9** WALL BASE DETAIL  
1 1/2" = 1'-0"




**8** WALL DETAIL  
1 1/2" = 1'-0"




**7** MEZZ. FLOOR-WALL DETAIL  
1 1/2" = 1'-0"




**6** ROOF DETAIL  
1 1/2" = 1'-0"



**13** MEZZAINE WALL DETAIL  
1 1/2" = 1'-0"



**12** MEZZAINE WALL DETAIL  
1 1/2" = 1'-0"



**11** MEZZAINE WALL DETAIL  
1 1/2" = 1'-0"



Consultant:

PRENTICE SCHOOL DISTRICT  
ADDITION AND REMODELING

Project Location: 1025 Town Street  
Prentice, WI 54556

DOOR-WINDOW DETAILS

Project Title:

HSR Project Number: 18022

Project Date: OCTOBER 19, 2018

Drawn By: MPL/JTD

Key Plan:

Revisions:


No.	Description	Date
1	ADD 1	10-25-18

Graphic Scale: VARIES


Last Update: 11/2/2018 10:57:34 AM

A510


BID PACKAGE 3  
ADDENDUM 2




**1** WDO. HEAD DETAIL  
1 1/2" = 1'-0"




**2** WDO. JAMB DETAIL  
1 1/2" = 1'-0"




**3** WDO. SILL DETAIL  
1 1/2" = 1'-0"




**4** DOOR HEAD DETAIL  
1 1/2" = 1'-0"




**5** DOOR JAMB DETAIL  
1 1/2" = 1'-0"




**6** DOOR SILL DETAIL  
1 1/2" = 1'-0"




**7** WDO. HEAD DETAIL  
1 1/2" = 1'-0"




**8** WDO. JAMB DETAIL  
1 1/2" = 1'-0"




**9** WDO. SILL DETAIL  
1 1/2" = 1'-0"




**10** DOOR HEAD DETAIL  
1 1/2" = 1'-0"




**11** DOOR JAMB DETAIL  
1 1/2" = 1'-0"




**12** DOOR SILL DETAIL  
1 1/2" = 1'-0"




**13** DOOR HEAD DETAIL  
1 1/2" = 1'-0"




**14** DOOR JAMB DETAIL  
1 1/2" = 1'-0"




**15** WDO. HEAD/ROOF DETAIL  
1 1/2" = 1'-0"



**16** WDO. JAMB DETAIL  
1 1/2" = 1'-0"



**17** WDO. SILL DETAIL  
1 1/2" = 1'-0"



**18** DOOR HEAD DETAIL  
1 1/2" = 1'-0"

**BID PACKAGE 3**



Consultant:

Project Title: PRENTICE SCHOOL DISTRICT  
ADDITION AND REMODELING

Project Location: 1025 Town Street  
Prentice, WI 54556

Sheet Title: DOOR-WINDOW DETAILS

HSR Project Number: 18022

Project Date: OCTOBER 19, 2018

Drawn By: MPL/JTD

Key Plan:

No.	Description	Date


Graphic Scale: VARIES

Last Update: 11/2/2018 10:57:38 AM


**A511**

BID PACKAGE 3  
ADDENDUM 2


**BID PACKAGE 3**




**5** WDO. HEAD DETAIL  
1 1/2" = 1'-0"




**4** WDO. JAMB DETAIL  
1 1/2" = 1'-0"




**3** WDO. HEAD/ROOF DETAIL  
1 1/2" = 1'-0"




**9** WDO. JAMB DETAIL  
1 1/2" = 1'-0"




**8** WDO. HEAD DETAIL  
1 1/2" = 1'-0"




**2** OH DOOR JAMB DETAIL  
1 1/2" = 1'-0"




**12** OH DOOR HEAD DETAIL  
1 1/2" = 1'-0"  
**ALTERNATE**




**13** OH DOOR JAMB DETAIL  
1 1/2" = 1'-0"  
**ALTERNATE**



**14** OH DOOR SILL DETAIL  
1 1/2" = 1'-0"  
**ALTERNATE**




**1** OH DOOR HEAD DETAIL  
1 1/2" = 1'-0"




**6** WDO. MULLION DETAIL  
1 1/2" = 1'-0"


**DETAIL 7 NOT USED**




**11** WDO. SILL DETAIL  
1 1/2" = 1'-0"




**10** WDO. MULLION/WALL DETAIL  
1 1/2" = 1'-0"




**17** WDO. SILL DETAIL  
1 1/2" = 1'-0"  
**ALTERNATE**




**18** DOOR HEAD/JAMB DETAIL  
1 1/2" = 1'-0"



**19** DOOR HEAD/JAMB DETAIL  
1 1/2" = 1'-0"



**15** WDO. HEAD DETAIL  
1 1/2" = 1'-0"  
**ALTERNATE**



**16** WDO. JAMB DETAIL  
1 1/2" = 1'-0"  
**ALTERNATE**



Consultant:

PRENTICE SCHOOL DISTRICT  
ADDITION AND REMODELING

Project Location: 1025 Town Street  
Prentice, WI 54556

Sheet Title: DOOR-WINDOW DETAILS

HSR Project Number: 18022

Project Date: OCTOBER 19, 2018

Drawn By: Author

Key Plan:


No.	Description	Date

Graphic Scale: VARIES


Last Update: 11/2/2018 10:57:42 AM

**A512**  
BID PACKAGE 3  
ADDENDUM 2


**BID PACKAGE 3**




**5** 149B 249A Dr Hd  
1 1/2" = 1'-0"




**4** DOOR JAMB DETAIL  
1 1/2" = 1'-0"




**3** 127A 143A Dr Jm 1  
1 1/2" = 1'-0"




**2** 127A 143A Dr Jm 2  
1 1/2" = 1'-0"




**1** 127A 143A Door Hd  
1 1/2" = 1'-0"




**10** 210 213 222 Dr SI 2  
1 1/2" = 1'-0"




**9** 210 213 222 Dr Hd  
1 1/2" = 1'-0"




**8** 149B Dr SI  
1 1/2" = 1'-0"




**7** DOOR JAMB DETAIL  
1 1/2" = 1'-0"




**6** 149B 249B Dr Jm 2  
1 1/2" = 1'-0"




**15** 239 Dr SI  
1 1/2" = 1'-0"




**14** DOOR JAMB DETAIL  
1 1/2" = 1'-0"




**13** 239 Dr Hd  
1 1/2" = 1'-0"




**12** 223 Dr SI  
1 1/2" = 1'-0"




**11** 223 Dr Hd  
1 1/2" = 1'-0"




**20** 253 DEF Dr SI  
1 1/2" = 1'-0"




**19** 253DEF Dr Hd  
1 1/2" = 1'-0"



**18** 253ABC SI  
1 1/2" = 1'-0"



**17** 253ABC Dr Jm  
1 1/2" = 1'-0"



**16** 253 ABC Hd  
1 1/2" = 1'-0"



Consultant:

Project Title: PRENTICE SCHOOL DISTRICT  
ADDITION AND REMODELING

Project Location: 1025 Town Street  
Prentice, WI 54556



Sheet Title: DOOR-WINDOW DETAILS

HSR Project Number: 18022

Project Date: OCTOBER 19, 2018

Drawn By: Author

Key Plan:




No.	Description	Date

Graphic Scale: VARIES


Last Update: 11/2/2018 10:57:44 AM

**A513**  
BID PACKAGE 3  
ADDENDUM 2


**BID PACKAGE 3**




**5** 280A Dr Sl  
1 1/2" = 1'-0"




**4** 280A Dr Jm  
1 1/2" = 1'-0"




**3** 280A Dr Hd  
1 1/2" = 1'-0"




**2** 270A Dr Sl  
1 1/2" = 1'-0"




**1** 270A Dr Hd  
1 1/2" = 1'-0"



**8** Ctr Dr Sl 233B  
1 1/2" = 1'-0"




**7** Ctr Dr Jm 233B  
1 1/2" = 1'-0"




**6** Ctr Dr hd 233B  
1 1/2" = 1'-0"




Consultant:




**1** WALL PLAN DETAIL  
1 1/2" = 1'-0"




**2** WALL PLAN DETAIL  
1 1/2" = 1'-0"




**3** ROOF LEADER DETAIL  
1 1/2" = 1'-0"




**4** ROOF LEADER DETAIL  
1 1/2" = 1'-0"




**5** ROOF LEADER DETAIL  
1 1/2" = 1'-0"




**6** ROOF LEADER DETAIL  
1 1/2" = 1'-0"




**7** LOUNGE COLUMN  
1 1/2" = 1'-0"




**8** RAISED FLOOR DETAIL  
1 1/2" = 1'-0"




**9** IN-FLOOR HEAT DETAIL  
1 1/2" = 1'-0"




**10** HEAD FLASHING DETAIL  
1" = 1'-0"




**11** OPENING JAMB DETAIL  
1 1/2" = 1'-0"




**12** BULKHEAD DETAIL  
1 1/2" = 1'-0"




**13** SKYLIGHT DETAIL  
1 1/2" = 1'-0"




**14** CEILING DETAIL  
1 1/2" = 1'-0"




**15** BULKHEAD DETAIL  
1 1/2" = 1'-0"



**16** BULKHEAD DETAIL  
1 1/2" = 1'-0"



**17** PRECAST OFFSET DETAIL  
1 1/2" = 1'-0"



**18** MTL PANEL-PRECAST DETAIL  
1 1/2" = 1'-0"

PRENTICE SCHOOL DISTRICT  
ADDITION AND REMODELING

Project Location: 1025 Town Street  
Prentice, WI 54556

MISC DETAILS

Project Title: PRENTICE SCHOOL DISTRICT  
ADDITION AND REMODELING

HSR Project Number: 18022

Project Date: OCTOBER 19, 2018

Drawn By: MPL/JTD

Key Plan:

No.	Description	Date

Graphic Scale: VARIES

Last Update: 11/2/2018 10:57:48 AM

**BID PACKAGE 3**

**A514**

BID PACKAGE 3  
ADDENDUM 2


























**HSR ASSOCIATES INC.**  
100 MILWAUKEE STREET  
LA CROSSE, WISCONSIN  
PHONE: 608.784.1830  
FAX: 608.782.5844  
www.hsrassociates.com

Consultant:  
**raSmith**  
CREATIVITY BEYOND ENGINEERING  
raSmith.com  
project number: 1180371  
5250 E. Terrace Dr., Ste. 108  
Madison, WI 53718-6343  
608.647.2024

Contractors are responsible for the means, methods, materials, techniques, and procedures of construction resulting, but not limited to, temporary supports, shoring, bracing, forming to support proposed loads and other similar items.



Project Title: **PRENTICE SCHOOL DISTRICT ADDITION AND REMODELING**

Project Location: **1025 Town Street Prentice, WI 54556**

Sheet Title: **FRAMING DETAILS**

Project Number: **18022**

Project Date: **OCTOBER 19, 2018**

Drawn By: **raSmith**

Key Plan:

No.	Description	Date
3	BP3 ADD2	11/2/18

Revisions:

Graphic Scale: **VARIES**

Last Update: **11/2/2018 10:28:45 AM**

No.	Description	Date
3	BP3 ADD2	11/2/18

**S810R**